

Standard Drive
S100



General

Product code		6033000500
Product description		LSLV0004S100-1EOFNS
Enclosure Rating		IP20, UL Type 1 (Optional)
Input Rating (3-Phase)	Supply Voltage [VAC]	-
	Rated Current [HD/Heavy Duty]	-
	Rated Current [ND/Normal Duty]	-
	Supply Frequency [Hz]	-
Input Rating (1-Phase)	Supply Voltage (VAC)	200~240 VAC
	Rated Current (HD)	4.4 A
	Rated Current (ND)	5.8 A
	Supply Frequency (Hz)	50~60 Hz
Output Rating (3-Phase Input)	Output Voltage (VAC)	200~240 VAC
	Motor Power HP (HD)	0.5 hp
	Motor Power HP (ND)	1.0 hp
	Motor Power kW (HD)	0.4 kW
	Motor Power kW (ND)	0.75 kW
	Output Current (HD)	2.5 A
	Output Current (ND)	3.1 A
	Rated Capacity (HD)	1.0 kVA
	Rated Capacity (ND)	1.2 kVA

	Output Frequency (Hz)	0~400 Hz
Output Rating (1-Phase Input)	Output Voltage [VAC]	-
	Motor Power HP [HD]	-
	Motor Power HP [ND]	-
	Output Current [HD]	-
	Output Current [ND]	-
	Rated Capacity [HD]	-
	Rated Capacity [ND]	-
	Output Frequency [Hz]	-

General

Short Circuit Rating		100kA (IEC 60439-1)
Overload Capacity	HD	150% for 1min
	ND	120% for 1min
Control Method		V/F control, Slip compensation, Sensorless vector, PM sensorless
Input Terminals		5 Points
Output Terminals	Relay Output	1 Point
	Open Collector Output	1 Point
EMC Filter		Built-in
DC Reactor		-
Communication	Built-in	Modbus RTU, LS INV 485
	Option	PROFINet, Modbus TCP, EtherCAT, EtherNet/IP, Profibus -DP, CANopen
Option Card		Extension I/O, Remote Cabel, Remote Keypad, Flange, C onduit

Environment


Ambient Temperature	HD	-10~50°C (14~122°F)
	ND	-10~40°C (14~104°F)
Storage Temperature		-20~65°C (-4~149°F)

Humidity	Relative humidity of 95% RH or below (without dew formation)
Vibration	9.8m/sec ² (1.0G) or below
Altitude	1,000m above sea level (From 1,000m or more, voltage/output current derating by 1% for every 100m elevation; up to 4,000m)
Certification	KC, CE, UL, cUL, Safety

Dimensions

Frame	A	
W x H x D	mm	68 x 180 x 130
	inch	2.68 x 7.09 x 5.12

Drawing



Dimension: mm (inch)